

Direct Thermal Barcode Label Printer



EC-3120D-USB

Features

- Support peel-off and tear off modes.
- Support Thermal Receipt Roll Paper & Label Paper.
- Support paper width from 16mm to 82mm.
- Support printer head pressure adjustment.
- Support paper auto verify.
- Automatical temperature control.
- Easy paper-roll installation.
- Easy paper jam clearance.
- Easy maintenance.



Specifications

Print method	Thermal line printing
Print speed	127mm/sec. (Max.); 101mm/sec. (Min.)
Paper width	16mm~82mm
Dot density	203dpi(8dots/mm)
Interface	Parallel/RS232C+USB/Ethernet
Reliability print	100Km
Power supply	DC 24V
Cash Drawer	DC 12-24V/1A
Temperature	0~50°C
Paper thickness	0.06~0.08mm
Dampness	10~80%
Barcode mode	CODE128, EAN128, ITF, CODE39, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPCA+2, UPCA+5, UPC-E, UPCE+2, UPC-E+5, CPOST, MSI, MSIC, PLESSEY, ITF14, EAN14
Drivers	Win9x/WinME/Win2000/WinNT/WinXP/Vista
Print command	compatible with TSC command set
External dimension	220*150*150mm(L*W*H)